

Type : 2EL071M6B-PD-A0-000**Date** : 12/08/2025

Power [kW] : 0.18
Input Voltage [V] : 400
Connection Type [Δ / Y] : Y
Frequency [Hz] : 50
Pole Number : 6
Nominal Speed [rpm] : 920
Nominal Current [A] : 0.60
Nominal Moment [Nm] : 1.86
Nominal Efficiency [η] : 64.5
Power Factor [$\cos\phi$] : 0.67
Locked Rotor Current [I_a/I_n] : 3.2
Locked Rotor Torque [M_a/M_n] : 1.9
Breakdown Torque [M_k/M_n] : 2.3
Motor Color : RAL 7031
Ambient Temperature : -15°C / +40°C

Efficiency Class : IE2
Duty Cycle : S1
Service Factor : 1.15
Frame Size : 071M
Weight [kg] : 5.90
Insulation Class : F [155°C]
Temperature Rise : B [80°K]
Protection Class : IP55
Vibration Severity Grade : A
Method of Cooling : IC411 (TEFC)
Direction of Rotation : Bidirectional
Balance : Half Key
Motor Thermal Protection : --
Altitude Above Sea Level : 1000m
Sound Pressure Level [dBA] : 42

ELECTRICAL DATA


Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	$\cos\phi$	CI
Δ	230	50	0.18	920	1.04	64.5	63.0	57.0	0.67	IE2
Y	400	50	0.18	920	0.60	64.5	63.0	57.0	0.67	IE2
Y	460	60	0.18	1125	0.54	67.2	65.0	59.8	0.62	IE2
Y	460	60	0.21	1120	0.59	67.3	65.2	60.1	0.66	IE2

MECHANICAL DATA

Moment of Inertia [kgm^2] : 0.00076
Bearing [DS / NS] : 6202ZZ C3 / 6202ZZ C3
Frame Material : Aluminum
Flange Type / Material : B3 / Aluminum
Cooling Fan Material : Plastic
End Shield Material : Aluminum

TERMINAL BOX

Terminal Box Material : Aluminum
Terminal Box Position : Top
Terminal Box Cable Entry : M20x1.5
Terminal Box Blind Cap : M16x1.5
Contact Screw Thread : M4

MECHANICAL DIMENSIONS

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO
COMMISSION REGULATION (EU) 2019/1781
THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 2EL071M6B-PD-A0-000

Date : 12/08/2025


NAMEPLATE DATA

Power [kW]	: 0.18	Nominal Speed [rpm]	: 920
Nominal Voltage [V]	: 400	Nominal Current [A]	: 0.60
Connection Type [Δ / Y]	: Y	Nominal Moment [Nm]	: 1.86
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 64.5

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	52.1	63.3
P ₂	50	100	53.1	48.5
P ₃	25	100	54.0	31.6
P ₄	90	50	37.9	54.3
P ₅	50	50	25.3	49.7
P ₆	50	25	23.4	35.3
P ₇	25	25	14.8	29.2

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 2EL071M6B-PD-A0-000

Torque and Current Curves Related to Speed



Motor Code : 2EL071M6B-PD-A0-000

Performance Curves Related to Rated Output

