

Type : 3EC132M4E-PD-B0-000**Date** : 12/08/2025

Power [kW] : 9.00
Input Voltage [V] : 400
Connection Type [Δ / Y] : Δ
Frequency [Hz] : 50
Pole Number : 4
Nominal Speed [rpm] : 1460
Nominal Current [A] : 17.9
Nominal Moment [Nm] : 58.9
Nominal Efficiency [η] : 90.8
Power Factor [$\cos\phi$] : 0.80
Locked Rotor Current [I_a/I_n] : 7.4
Locked Rotor Torque [M_a/M_n] : 3.1
Breakdown Torque [M_k/M_n] : 3.4
Motor Color : RAL 7031
Ambient Temperature : -15°C / +40°C

Efficiency Class : IE3
Duty Cycle : S1
Service Factor : --
Frame Size : 132M
Weight [kg] : 62.0
Insulation Class : F [155°C]
Temperature Rise : B [80°K]
Protection Class : IP55
Vibration Severity Grade : A
Method of Cooling : IC411 (TEFC)
Direction of Rotation : Bidirectional
Balance : Half Key
Motor Thermal Protection : --
Altitude Above Sea Level : 1000m
Sound Pressure Level [dBA] : 64

ELECTRICAL DATA


Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	$\cos\phi$	CI
Δ	400	50	9.00	1460	17.9	90.8	91.6	91.2	0.80	IE3
Y	690	50	9.00	1460	10.3	90.8	91.6	91.2	0.80	IE3

MECHANICAL DATA

Moment of Inertia [kgm²] : 0.03600
Bearing [DS / NS] : 6208ZZ C3 / 6208ZZ C3
Frame Material : Aluminum
Flange Type / Material : B3 / Aluminum
Cooling Fan Material : Plastic
End Shield Material : Aluminum

TERMINAL BOX

Terminal Box Material : Aluminum
Terminal Box Position : Top
Terminal Box Cable Entry : M25x1.5
Terminal Box Blind Cap : M25x1.5
Contact Screw Thread : M5

MECHANICAL DIMENSIONS

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO
COMMISSION REGULATION (EU) 2019/1781
THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EC132M4E-PD-B0-000

Date : 12/08/2025


NAMEPLATE DATA

Power [kW]	: 9.00	Nominal Speed [rpm]	: 1460
Nominal Voltage [V]	: 400	Nominal Current [A]	: 17.9
Connection Type [Δ / Y]	: Δ	Nominal Moment [Nm]	: 58.9
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 90.8

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	10.9	89.2
P ₂	50	100	8.3	85.8
P ₃	25	100	7.4	77.1
P ₄	90	50	6.6	87.2
P ₅	50	50	4.0	86.3
P ₆	50	25	3.0	80.6
P ₇	25	25	1.9	76.8

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]




Manufactured and tested in accordance with IEC 60034

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EC132M4E-PD-B0-000



Motor Code : 3EC132M4E-PD-B0-000

Performance Curves Related to Rated Output

