

Type : 3EL160L4E-PD-BA-000

Date : 04/11/2025

Power [kW]	: 15.0	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 160L
Pole Number	: 4	Weight [kg]	: 97.5
Nominal Speed [rpm]	: 1465	Insulation Class	: F [155°C]
Nominal Current [A]	: 28.7	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 97.8	Protection Class	: IP55
Nominal Efficiency [η]	: 92.1	Vibration Severity Grade	: A
Power Factor [$\cos\phi$]	: 0.82	Method of Cooling	: IC411 (TEFC)
Locked Rotor Current [I_a/I_n]	: 7.8	Direction of Rotation	: Bidirectional
Locked Rotor Torque [M_a/M_n]	: 2.8	Balance	: Half Key
Breakdown Torque [M_k/M_n]	: 3.5	Motor Thermal Protection	: PTC
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 63

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	$\cos\phi$	Cl
Δ	400	50	15.0	1465	28.7	92.1	92.4	91.9	0.82	IE3
Y	690	50	15.0	1465	16.6	92.1	92.4	91.9	0.82	IE3
Δ	460	60	15.0	1770	25.0	93.0	93.1	92.4	0.81	IE3
Δ	460	60	17.4	1760	28.5	92.4	92.5	92.0	0.83	IE2


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.08579
Bearing [DS / NS]	: 6309ZZ C3 / 6209ZZ C3
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: 2xM32x1.5
Terminal Box Blind Cap	: --
Contact Screw Thread	: M6

MECHANICAL DIMENSIONS




Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.





ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO
COMMISSION REGULATION (EU) 2019/1781
THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EL160L4E-PD-BA-000

Date : 04/11/2025


NAMEPLATE DATA

Power [kW]	: 15.0	Nominal Speed [rpm]	: 1465
Nominal Voltage [V]	: 400	Nominal Current [A]	: 28.7
Connection Type [Δ / Y]	: Δ	Nominal Moment [Nm]	: 97.8
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 92.1

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	8.2	91.7
P ₂	50	100	6.2	89.0
P ₃	25	100	5.6	81.6
P ₄	90	50	5.1	89.9
P ₅	50	50	3.0	89.2
P ₆	50	25	2.2	84.9
P ₇	25	25	1.3	82.3

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EL160L4E-PD-BA-000

Torque and Current Curves Related to Speed



Motor Code : 3EL160L4E-PD-BA-000

Performance Curves Related to Rated Output

