

Type : 3EL250M2C-PD-BA-000

Date : 12/08/2025

Power [kW] : 55.0
Input Voltage [V] : 400
Connection Type [Δ / Y] : Δ
Frequency [Hz] : 50
Pole Number : 2
Nominal Speed [rpm] : 2970
Nominal Current [A] : 93.3
Nominal Moment [Nm] : 177
Nominal Efficiency [η] : 94.4
Power Factor [cosφ] : 0.90
Locked Rotor Current [Ia/In] : 8.6
Locked Rotor Torque [Ma/Mn] : 3.3
Breakdown Torque [Mk/Mn] : 3.4
Motor Color : RAL 7031
Ambient Temperature : -15°C / +40°C

Efficiency Class : IE3
Duty Cycle : S1
Service Factor : 1.20
Frame Size : 250M
Weight [kg] :
Insulation Class : F [155°C]
Temperature Rise : B [80°K]
Protection Class : IP55
Vibration Severity Grade : A
Method of Cooling : IC411 (TEFC)
Direction of Rotation : Bidirectional
Balance : Half Key
Motor Thermal Protection : PTC
Altitude Above Sea Level : 1000m
Sound Pressure Level [dBA] : 75

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	Cosφ	CI
Δ	400	50	55.0	2970	93.3	94.4	94.8	94.5	0.90	IE3
Y	690	50	55.0	2970	53.9	94.4	94.8	94.5	0.90	IE3
Δ	460	60	55.0	3570	81.6	93.6	94.1	93.7	0.90	IE3
Δ	460	60	63.8	3560	93.6	94.0	94.5	94.1	0.91	IE3


MECHANICAL DATA

Moment of Inertia [kgm²] : 0.38000
Bearing [DS / NS] : 6315ZZ C3 / 6215ZZ C3
Frame Material : Aluminum
Flange Type / Material : B3 / Aluminum
Cooling Fan Material : Plastic
End Shield Material : Aluminum

TERMINAL BOX

Terminal Box Material : Aluminum
Terminal Box Position : Top
Terminal Box Cable Entry : M12x1.5+2xM50x1.5
Terminal Box Blind Cap : --
Contact Screw Thread : M10

MECHANICAL DIMENSIONS



Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO COMMISSION REGULATION (EU) 2019/1781 THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EL250M2C-PD-BA-000

Date : 12/08/2025


NAMEPLATE DATA

Power [kW]	: 55.0	Nominal Speed [rpm]	: 2970
Nominal Voltage [V]	: 400	Nominal Current [A]	: 93.3
Connection Type [Δ / Y]	: Δ	Nominal Moment [Nm]	: 177
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 94.4

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	5.9	93.9
P ₂	50	100	4.0	92.6
P ₃	25	100	3.3	88.2
P ₄	90	50	4.0	91.9
P ₅	50	50	2.1	92.4
P ₆	50	25	1.5	89.0
P ₇	25	25	0.8	89.0

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EL250M2C-PD-BA-000

Torque and Current Curves Related to Speed



Motor Code : 3EL250M2C-PD-BA-000

Performance Curves Related to Rated Output

